



ICONIC BRANDS, LEADING INNOVATION

Refrigerators & Freezers

Merchandisers

Chest Freezers

Ice Cream Dipping Cabinets & Display Freezers

Prep Tables

Chef Bases

Milk Coolers

Bottle Coolers

Beer Tower Dispensers



REACH-IN REFRIGERATORS & FREEZERS	3
MERCHANDISERS	10
UNDERCOUNTER REFRIGERATORS & FREEZERS	18
CHEST FREEZERS	21
ICE CREAM DIPPING CABINETS & DISPLAY FREEZERS	25
SANDWICH/SALAD, MEGATOP & PIZZA PREP TABLES	29
CHEF BASES	35
MILK COOLERS	37
BOTTLE COOLERS & BEER TOWER DISPENSERS	39



SUPPORT

Maxx Cold Customer Support

3355 Enterprise Avenue, Suite 160
Weston, FL 33331
Tel: 954-202-7419
Fax: 954-202-7337
Office Hours: Monday - Friday 8:30am to 5:30pm EST

Send orders to: Orders@TheLegacyCompanies.com

Technical Support (MaxxHelp):

TechnicalServices@TheLegacyCompanies.com

International Support:

Sales@GreenfieldWorldTrade.com

Parts:

Email: CustomerService@Partstown.com
Phone: (800) 438-8898
Web: www.partstown.com/maxx_cold/parts
Hours Available (EST) Monday - Friday 7:00am to 7:00pm

WARRANTY

Maxx Cold Warranty (USA / CANADA)

Contact Maxx Cold for warranty statement at: TechnicalServices@TheLegacyCompanies.com or 877-368-2797



YOU'RE ALWAYS COOL WHEN YOU CHOOSE MAXX COLD FOODSERVICE EQUIPMENT.

Engineered to provide you the best value, Maxx Cold commercial foodservice equipment is designed to provide you with safe, reliable and durable refrigerators, freezers, prep tables and merchandisers to ensure your restaurant and hospitality needs are exceeded. Choose from Maxx Cold, X-Series or Select Series to depend on!



Exterior Construction	Stainless Steel	Stainless Steel	Stainless Steel
Interior Construction	Stainless Steel	Aluminum	Aluminum
Available Door Types	Solid Door Stainless Steel	Solid Door Stainless Steel & Glass Door	Solid Door Stainless Steel & Glass Door
Door Handle	Recessed Black Plastic Handles	Recessed Black Plastic Handles	Formed Full Length Handles
Compressor Mounting	Top & Bottom Mount	Top Mount	Bottom Mount
Interior Lighting	LED Lighting	LED Lighting	LED Lighting
Maximum Height	82.25"	82.75"	79.7"
Digital Control / Display	LED Display	LED Display	LED Display
Shelving	PE Coated Wire Shelves (3 per section / door)	PE Coated Wire Shelves (3 per section / door)	PE Coated Wire Shelves (3 per section / door)
Casters	5" Swivel Casters	4" Swivel Casters	4" Swivel Casters
Security	Lock & Key Set	Lock & Key Set	Lock & Key Set
International Electrical*	Units available in 220V/50-60Hz/1Ph	Units available in 220V/50-60Hz/1Ph	Units available in 220V/50-60Hz/1Ph
Certifications	ETL Tested to NSF & UL Standards, Energy Star	ETL Tested to NSF & UL Standards, Energy Star	ETL Tested to NSF & UL Standards, Energy Star
Value	Premium	Classic Value	Economy

*Please specify when ordering if international electrical requirements are needed.



 **MAXX COLD**

 **MAXX COLD**
X-series

 **MAXX COLD**
SELECT SERIES

REFRIGERATORS & FREEZERS

Maxx Cold offers a robust line of refrigeration options to meet any budget or application. Choose from an array of refrigerators and freezers including 1, 2 and 3 door upright units featuring stainless steel, glass doors in either top or bottom mount designs. Undercounter models, as well as solid and glass-top Chest Freezers are also available.

BOTTOM-MOUNT REACH-IN REFRIGERATORS & FREEZERS



MCR-23FDHC
MCF-23FDHC
26.75"W x 31"D x 82.75"H



MCR-49FDHC
MCF-49FDHC
54"W x 31"D x 82.75"H



MCR-72FDHC
MCF-72FDHC
81"W x 31"D x 82.75"H

Refrigerators:

MCR-23FDHC - Upright reach-in refrigerator; stainless steel exterior

MCR-49FDHC - Upright reach-in refrigerator; stainless steel exterior

MCR-72FDHC - Upright reach-in refrigerator; stainless steel exterior

Freezers:

MCF-23FDHC - Upright reach-in freezer; stainless steel exterior

MCF-49FDHC - Upright reach-in freezer; stainless steel exterior

MCF-72FDHC - Upright reach-in freezer; stainless steel exterior

All Models Feature:

- Self-closing door(s) with easy to grip recessed handle(s)
- Automatic interior lighting
- Lock and key set for security
- Equipped with four (4) or six (6) 5" diameter swivel casters
- Electronic control panel with digital display
- Automatic defrost system
- Open door alert beeps if door has been open for five minutes
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Polyurethane foam insulation provides outstanding thermal regulation and energy efficiency



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	HP	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MCR-23FDHC	26.75" x 31" x 82.75" (680 x 787 x 2102 mm)	22.8" x 24.1" x 53.7" (578 x 613 x 1364 mm)	18.9 Cu Ft (535 L)	33°F to 41°F (1°C to 5°C)	2.0A	1/4	271 lbs (123 kg)	R-290a 2.53 oz (72 g)	1 / 3	115V / 60Hz / 1Ph
MCR-49FDHC	54" x 31" x 82.75" (1372 x 787 x 2102 mm)	49.8" x 24.1" x 53.7" (1264 x 613 x 1364 mm)	42.8 Cu Ft (1212 L)	33°F to 41°F (1°C to 5°C)	2.4A	1/4	397 lbs (180 kg)	R-290a 3.46 oz (98 g)	2 / 6	115V / 60Hz / 1Ph
MCR-72FDHC	81" x 31" x 82.75" (2057 x 787 x 2102 mm)	77.3" x 24.1" x 53.7" (1963 x 613 x 1364 mm)	66.7 Cu Ft (1889 L)	33°F to 41°F (1°C to 5°C)	5.5A	1/2	634 lbs (287 kg)	R-290a 5.22 oz (148 g)	3 / 9	115V / 60Hz / 1Ph
MCF-23FDHC	26.75" x 31" x 82.75" (680 x 787 x 2102 mm)	22.8" x 24.1" x 53.7" (578 x 613 x 1364 mm)	18.9 Cu Ft (535 L)	-10°F to 10°F (-23°C to -12°C)	5.6A	1/2	284 lbs (129 kg)	R-290a 2.33 oz (66 g)	1 / 3	115V / 60Hz / 1Ph
MCF-49FDHC	54" x 31" x 82.75" (1372 x 787 x 2102 mm)	49.8" x 24.1" x 53.7" (1264 x 613 x 1364 mm)	42.8 Cu Ft (1212 L)	-10°F to 10°F (-23°C to -12°C)	4.6A	1/2	403 lbs (183 kg)	R-290a 4.44 oz (126 g)	2 / 6	115V / 60Hz / 1Ph
MCF-72FDHC	81" x 31" x 82.75" (2057 x 787 x 2102 mm)	77.3" x 24.1" x 53.7" (1963 x 613 x 1364 mm)	66.7 Cu Ft (1889 L)	-10°F to 10°F (-23°C to -12°C)	9.9A	1	650 lbs (295 kg)	R-290a 5.08 oz (144 g)	3 / 9	220V / 60Hz / 1Ph



MCRT-23FDHC
MCFT-23FDHC
26.75"W x 31"D x 82.75"H



MCRT-49FDHC
MCFT-49FDHC
54"W x 31"D x 82.75"H



MCRT-72FDHC
MCFT-72FDHC
81"W x 31"D x 82.75"H

Refrigerators:

MCRT-23FDHC - Upright reach-in refrigerator; stainless steel exterior

MCRT-49FDHC - Upright reach-in refrigerator; stainless steel exterior

MCRT-72FDHC* - Upright reach-in refrigerator; stainless steel exterior

Freezers:

MCFT-23FDHC - Upright reach-in freezer; stainless steel exterior

MCFT-49FDHC - Upright reach-in freezer; stainless steel exterior

MCFT-72FDHC - Upright reach-in freezer; stainless steel exterior

All Models Feature:

- Self-closing door(s) with easy to grip recessed handle(s)
- Automatic interior lighting
- Lock and key set for security
- Supplied with four (4) or six (6) 5" diameter swivel casters
- Electronic control panel with digital display
- Automatic defrost system
- Open door alert beeps if door has been open for five minutes
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Polyurethane foam insulation provides outstanding thermal regulation and energy efficiency



*MCRT-72FDHC not Energy Star Listed

MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	HP	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MCRT-23FDHC	27" x 31" x 82" (681 x 787 x 2078 mm)	22.8" x 24.1" x 53.7" (578 x 613 x 1364 mm)	18.9 Cu Ft (535 L)	33°F to 41°F (1°C to 5°C)	3.0A	1/4	264 lbs (120 kg)	R-290a 2.61 oz (74 g)	1 / 3	115V / 60Hz / 1Ph
MCRT-49FDHC	54" x 31" x 82" (1370 x 787 x 2078 mm)	49.8" x 24.1" x 53.7" (1264 x 613 x 1364 mm)	42.8 Cu Ft (1212 L)	33°F to 41°F (1°C to 5°C)	3.2A	1/4	388 lbs (190 kg)	R-290a 3.67 oz (104 g)	2 / 6	115V / 60Hz / 1Ph
MCRT-72FDHC	81" x 31" x 82" (2060 x 787 x 2078 mm)	77.3" x 24.1" x 53.7" (1963 x 613 x 1364 mm)	66.7 Cu Ft (1889 L)	33°F to 41°F (1°C to 5°C)	6.3A	1/2	567 lbs (257 kg)	R-290a 5.22 oz (148 g)	3 / 9	115V / 60Hz / 1Ph
MCFT-23FDHC	27" x 31" x 82" (681 x 787 x 2078 mm)	22.8" x 24.1" x 53.7" (578 x 613 x 1364 mm)	18.9 Cu Ft (535 L)	-10°F to 10°F (-23°C to -12°C)	4.9A	1/4	273 lbs (124 kg)	R-290a 2.82 oz (80 g)	1 / 3	115V / 60Hz / 1Ph
MCFT-49FDHC	54" x 31" x 82" (1370 x 787 x 2078 mm)	49.8" x 24.1" x 53.7" (1264 x 613 x 1364 mm)	42.8 Cu Ft (1212 L)	-10°F to 10°F (-23°C to -12°C)	6.8A	1/4	418 lbs (190 kg)	R-290a 4.44 oz (126 g)	2 / 6	115V / 60Hz / 1Ph
MCFT-72FDHC	81" x 31" x 82" (2060 x 787 x 2078 mm)	77.3" x 24.1" x 53.7" (1963 x 613 x 1364 mm)	66.7 Cu Ft (1889 L)	-10°F to 10°F (-23°C to -12°C)	8.4A	1/2	595 lbs (270 kg)	R-290a 5.22 oz (148 g)	3 / 9	220V / 60Hz / 1Ph

TOP-MOUNT REACH-IN REFRIGERATORS & FREEZERS



MXCR-19FDHC
MXCF-19FDHC

26.75"W x 31.5"D x 77.6"H



MXCR-23FDHC
MXCF-23FDHC

26.75"W x 32.7"D x 82.25"H



MXCR-49FDHC
MXCF-49FDHC

54"W x 32.7"D x 82.25"H



MXCR-72FDHC
MXCF-72FDHC

81"W x 32.7"D x 82.25"H

Refrigerators:

MXCR-19FDHC - Upright reach-in refrigerator; stainless steel exterior

MXCR-23FDHC - Upright reach-in refrigerator; stainless steel exterior

MXCR-49FDHC - Upright reach-in refrigerator; stainless steel exterior

MXCR-72FDHC - Upright reach-in refrigerator; stainless steel exterior

Freezers:

MXCF-19FDHC - Upright reach-in freezer; stainless steel exterior

MXCF-23FDHC - Upright reach-in freezer; stainless steel exterior

MXCF-49FDHC - Upright reach-in freezer; stainless steel exterior

MXCF-72FDHC - Upright reach-in freezer; stainless steel exterior

All Models Feature:

- Self-closing door(s) with easy to grip recessed handle(s)
- Field reversible door (single door models only)
- Automatic interior lighting
- Lock and key set for security
- Equipped with four (4) or six (6) 5" diameter swivel casters
- Electronic control panel with digital display
- Automatic defrost system
- Open door alert beeps if door has been open for three minutes
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXCR-19FDHC	25.2" x 31.5" x 77.6" (640 x 800 x 1970 mm)	20.25" x 28.7" x 61.8" (514 x 730 x 1570 mm)	19 Cu Ft (538 L)	34°F to 41°F (1°C to 5°C)	3A	291 lbs (132 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXCR-23FDHC	26.8" x 32.7" x 82.25" (681 x 831 x 2090 mm)	21.9" x 26.5" x 52.1" (556 x 673 x 1324 mm)	23 Cu Ft (651 L)	34°F to 41°F (1°C to 5°C)	3A	311 lbs (143 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXCR-49FDHC	53.9" x 32.7" x 82.25" (1369 x 831 x 2090 mm)	49.1" x 26.5" x 52.1" (1246 x 673 x 1324 mm)	49 Cu Ft (1387 L)	34°F to 41°F (1°C to 5°C)	4.5A	536 lbs (244 kg)	R-290A 3.7 oz (105 g)	2 / 6	115V / 60Hz / 1Ph
MXCR-72FDHC	81" x 32.7" x 82.25" (2057 x 831 x 2090 mm)	76.1" x 26.5" x 52.1" (1933 x 673 x 1324 mm)	72 Cu Ft (2039 L)	34°F to 41°F (1°C to 5°C)	7A	639 lbs (291 kg)	R-290A 5.29 oz (150 g)	3 / 9	220V / 60Hz / 1Ph
MXCF-19FDHC	25.2" x 31.5" x 77.6" (640 x 800 x 1970 mm)	20.25" x 28.7" x 61.8" (514 x 730 x 1570 mm)	19 Cu Ft (538 L)	-10°F to 10°F (-23°C to -12°C)	8A	296 lbs (134 kg)	R-290A 3.88 oz (110 g)	1 / 3	115V / 60Hz / 1Ph
MXCF-23FDHC	26.8" x 32.7" x 82.25" (681 x 831 x 2090 mm)	21.9" x 26.5" x 52.1" (556 x 673 x 1324 mm)	23 Cu Ft (651 L)	-10°F to 10°F (-23°C to -12°C)	8A	336 lbs (140 kg)	R-290A 3.88 oz (110 g)	1 / 3	115V / 60Hz / 1Ph
MXCF-49FDHC	53.9" x 32.7" x 82.25" (1369 x 831 x 2090 mm)	49.1" x 26.5" x 52.1" (1246 x 673 x 1324 mm)	49 Cu Ft (1387 L)	-10°F to 10°F (-23°C to -12°C)	9A	502 lbs (160 kg)	R-290A 5.29oz (150 g)	2 / 6	115V / 60Hz / 1Ph
MXCF-72FDHC	81" x 32.7" x 82.25" (2057 x 831 x 2090 mm)	76.1" x 26.5" x 52.1" (1933 x 673 x 1324 mm)	72 Cu Ft (2039 L)	-10°F to 10°F (-23°C to -12°C)	9A	601 lbs (195 kg)	R-290A 5.29oz (150 g)	3 / 9	230V / 60Hz / 1Ph



MXCR-23GDHC
26.8"W x 31.9"D x 82.3"H



MXCR-49GDHC
53.9"W x 31.9"D x 82.3"H

Models:

MXCR-23GDHC - Glass door reach-in refrigerator; stainless steel exterior

MXCR-49GDHC - Glass door reach-in refrigerator; stainless steel exterior

All Models Feature:

- Durable, easy to clean stainless steel exterior and interior
- Self-closing, locking, dual-pane glass doors with easy to grip handles
- Adjustable heavy-duty wire shelves (3 per section/door)
- Open door alert beeps when door has been open for 3 minutes
- Equipped with four 4" swivel casters (2 with brakes)
- Digital control system
- LED interior lighting & temperature display
- Automatic defrost system
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXCR-23GDHC	26.8" x 31.9" x 82.3" (681 x 810 x 2090 mm)	22.2" x 27.6" x 50.2" (564 x 700 x 1276 mm)	23 Cu Ft (651 L)	34°F to 41°F (1°C to 5°C)	3A	366 lbs (166 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXCR-49GDHC	53.9" x 31.9" x 82.3" (1369 x 810 x 2090 mm)	49.4" x 27.6" x 50.2" (1254 x 700 x 1276 mm)	49 Cu Ft (1387 L)	34°F to 41°F (1°C to 5°C)	4.5A	597 lbs (272 kg)	R-290A 3.7 oz (105 g)	2 / 6	115V / 60Hz / 1Ph

REACH-IN REFRIGERATORS & FREEZERS



MXR-23RHC
30.6"W x 29"D x 78"H



MXR-23FHC
30.6"W x 29"D x 78"H

Refrigerator:

MXR-23RHC - Economy reach-in refrigerator; painted steel exterior

Freezer:

MXR-23FHC - Economy reach-in freezer; painted steel exterior

All Models Feature:

- Easy to clean, low maintenance white painted steel exterior and white painted aluminum interior
- Field-reversible hinged door with heavy-duty recessed full-length handle
- Door lock & key set for security
- Three (3) adjustable wire shelves, one (1) fixed half shelf
- Equipped with 2.5" swivel casters (2 with brakes)
- Digital control system
- LED temperature display
- Automatic defrost system
- Door frame heaters
- Easy to clean/replace removable snap-in gaskets
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Front-breathing bottom-mounted condensing unit
- Urethane foam insulated walls
- Not equipped with interior lighting



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXR-23RHC	30.6" x 29" x 78" (777 x 737 x 1981 mm)	26.3" x 21.6" x 58.9" (668 x 549 x 1496 mm)	23 Cu Ft (651 L)	34°F to 41°F (1°C to 5°C)	3.0A	264 lbs (120 kg)	R-290A 3.35 oz (95 g)	1 / 3	115V / 60Hz / 1Ph
MXR-23FHC	30.6" x 29" x 78" (777 x 737 x 1981 mm)	26.3" x 21.6" x 58.9" (668 x 549 x 1496 mm)	23 Cu Ft (651 L)	-10°F to 10°F (-23°C to -12°C)	7.0A	286 lbs (130 kg)	R-290A 4.23oz (120 g)	1 / 3	115V / 60Hz / 1Ph



MXSR-23FDHC
MXSF-23FDHC
27"W x 32.5"D x 79.7"H



MXSR-49FDHC
MXSF-49FDHC
54.1"W x 32.5"D x 79.7"H



MXSR-23GDHC
27"W x 32.5"D x 79.7"H



MXSR-49GDHC
54.1"W x 32.5"D x 79.7"H

Solid Door Models:

Refrigerators:

MXSR-23FDHC - Upright reach-in refrigerator; stainless steel exterior

MXSR-49FDHC - Upright reach-in refrigerator; stainless steel exterior

Freezers:

MXSF-23FDHC - Upright reach-in freezer; stainless steel exterior

MXSF-49FDHC - Upright reach-in freezer; stainless steel exterior

Glass Door Models:

MXSR-23GDHC - Glass door reach-in refrigerator; stainless steel exterior

MXSR-49GDHC - Glass door reach-in refrigerator; stainless steel exterior

All Models Feature:

- Stainless Steel Exterior
- Solid Door Interior: Painted Aluminum
- Glass Door Interior: Stainless Steel
- Interior lighting controlled by an automatic on-off door switch
- Field reversible door (single door models only)
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Equipped with door locks and 4" diameter swivel casters (2 with brakes)
- Self-contained, digitally-controlled heavy-duty refrigeration system - forced air for even temperature regulation
- Automatic defrost system
- Self-closing doors with heavy-duty hinges that open to 180°
- Heavy-duty corrosion-resistant shelves and adjustable mounting clips
- Open door alert beeps when door has been open for 3 minutes
- Easy to full-length formed handles



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXSR-23FDHC	27" x 32.5" x 79.7" (686 x 825 x 2025 mm)	22.3" x 26.8" x 55" (566 x 680 x 1397 mm)	19.3 Cu Ft (547 L)	33°F to 41°F (1°C to 5°C)	2.8A	300 lbs (136 kg)	R-290a	1 / 3	115V / 60Hz / 1Ph
MXSR-49FDHC	54.1" x 32.5" x 79.7" (1372 x 825 x 2025 mm)	49.3" x 26.8" x 55" (1252 x 680 x 1397 mm)	42.9 Cu Ft (1215 L)	33°F to 41°F (1°C to 5°C)	6.25A	430 lbs (195 kg)	R-290a	2 / 6	115V / 60Hz / 1Ph
MXSF-23FDHC	27" x 32.5" x 79.7" (686 x 825 x 2025 mm)	22.3" x 26.8" x 55" (566 x 680 x 1397 mm)	19.3 Cu Ft (547 L)	-10°F to 10°F (-24°C to -12°C)	6A	310 lbs (141 kg)	R-290a	1 / 3	115V / 60Hz / 1Ph
MXSF-49FDHC	54.1" x 32.5" x 79.7" (1372 x 825 x 2025 mm)	49.3" x 26.8" x 55" (1252 x 680 x 1397 mm)	42.9 Cu Ft (1215 L)	-10°F to 10°F (-24°C to -12°C)	9A	460 lbs (209 kg)	R-290a	2 / 6	115V / 60Hz / 1Ph
MXSR-23GDHC	27" x 32.5" x 79.7" (686 x 825 x 2025 mm)	22.3" x 26.8" x 55" (566 x 680 x 1397 mm)	19.3 Cu Ft (547 L)	33°F to 41°F (1°C to 5°C)	2.8A	280 lbs (127 kg)	R-290a	1 / 3	115V / 60Hz / 1Ph
MXSR-48GDHC	54.1" x 32.5" x 79.7" (1372 x 825 x 2025 mm)	49.3" x 26.8" x 55" (1252 x 680 x 1397 mm)	42.9 Cu Ft (1215 L)	33°F to 41°F (1°C to 5°C)	6.25A	440 lbs (200 kg)	R-290a	2 / 6	115V / 60Hz / 1Ph



MERCHANDISERS

Showcase your cold beverages, food products and grab and go items with Maxx Cold Merchandisers. Our glass door Merchandisers provide excellent product visibility to help boost impulse sales, keep product at the right temperature and are energy efficient.



MXM1-12RHC
25"W x 26"D x 62"H



MXM1-12RBHC
25"W x 26"D x 62"H



MXM1-16RHC
25"W x 26"D x 74.5"H



MXM1-16RBHC
25"W x 26"D x 74.5"H



MXM1-23RHC
27"W x 32"D x 79.5"H



MXM1-23RBHC
27"W x 32"D x 79.5"H

Models:

MXM1-12RHC - Reach-in refrigerator; white coated steel exterior

MXM1-12RBHC - Reach-in refrigerator; black coated steel exterior

MXM1-16RHC - Reach-in refrigerator; white coated steel exterior

MXM1-16RBHC - Reach-in refrigerator; black coated steel exterior

MXM1-23RHC - Reach-in refrigerator; white coated steel exterior

MXM1-23RBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with three (3) or four (4) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-12RHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	221 lbs (100 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-12RBHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	221 lbs (100 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16RHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.0A	243 lbs (110 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16RBHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.0A	243 lbs (110 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-23RHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	33°F to 41°F (1°C to 5°C)	3.0A	325 lbs (148 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph
MXM1-23RBHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	33°F to 41°F (1°C to 5°C)	3.0A	325 lbs (148 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph

UPRIGHT MERCHANDISER REFRIGERATORS



MXM2-48RHC
54"W x 32"D x 79.5"H



MXM2-48RBHC
54"W x 32"D x 79.5"H



MXM3-72RHC
81"W x 32"D x 79.5"H



MXM3-72RBHC
81"W x 32"D x 79.5"H

Models:

MXM2-48RHC - Reach-in refrigerator; white coated steel exterior

MXM2-48RBHC - Reach-in refrigerator; black coated steel exterior

MXM3-72RHC - Reach-in refrigerator; white coated steel exterior

MXM3-72RBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with eight (8) or twelve (12) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) or six (6) low profile (1.125" x 1.625") rollers (2 or 3 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48RHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48RBHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM3-72RHC	81" x 32" x 79.5" (2057 x 810 x 2019 mm)	72.25" x 26.5" x 52.25" (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	33°F to 41°F (1°C to 5°C)	7.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph
MXM3-72RBHC	81" x 32" x 79.5" (2057 x 810 x 2019 mm)	72.25" x 26.5" x 52.25" (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	33°F to 41°F (1°C to 5°C)	7.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph



MXM2-48RSHC
54"W x 32"D x 79.5"H



MXM2-48RSBHC
54"W x 32"D x 79.5"H

Models:

MXM2-48RSHC - Reach-in sliding door refrigerator; white coated steel exterior

MXM2-48RSBHC - Reach-in sliding door refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Supplied with eight (8) adjustable heavy-duty PE-coated wire shelves
- Equipped with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48RSHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Sliding / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48RSBHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Sliding / 8 Shelves	115V / 60Hz / 1Ph

UPRIGHT MERCHANDISER FREEZERS



MXM1-12FHC
25"W x 26"D x 62"H



MXM1-12FBHC
25"W x 26"D x 62"H



MXM1-16FHC
25"W x 26"D x 74.5"H



MXM1-16FBHC
25"W x 26"D x 74.5"H



MXM1-23FHC
27"W x 32"D x 79.5"H



MXM1-23FBHC
27"W x 32"D x 79.5"H

Models:

MXM1-12FHC - Reach-in freezer; white coated steel exterior

MXM1-12FBHC - Reach-in freezer; black coated steel exterior

MXM1-16FHC - Reach-in freezer; white coated steel exterior

MXM1-16FBHC - Reach-in freezer; black coated steel exterior

MXM1-23FHC - Reach-in freezer; white coated steel exterior

MXM1-23FBHC - Reach-in freezer; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Triple pane heated & insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with three (3) or four (4) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-12FHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	0°F to 10°F (-18°C to -12°C)	5.0A	221 lbs (100 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-12FBHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	0°F to 10°F (-18°C to -12°C)	5.0A	221 lbs (100 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16FHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	0°F to 10°F (-18°C to -12°C)	5.0A	243 lbs (110 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16FBHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	0°F to 10°F (-18°C to -12°C)	5.0A	243 lbs (110 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-23FHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	0°F to 10°F (-18°C to -12°C)	8.0A	325 lbs (148 kg)	R-290A 3.88 oz (110 g)	1 / 4	115V / 60Hz / 1Ph
MXM1-23FBHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	0°F to 10°F (-18°C to -12°C)	8.0A	325 lbs (148 kg)	R-290A 3.88 oz (110 g)	1 / 4	115V / 60Hz / 1Ph



MXM2-48FHC
54"W x 32"D x 79.5"H



MXM2-48FBHC
54"W x 32"D x 79.5"H



MXM3-72FHC
81"W x 32"D x 79.5"H



MXM3-72FBHC
81"W x 32"D x 79.5"H

Models:

MXM2-48FHC - Reach-in freezer; white coated steel exterior

MXM2-48FBHC - Reach-in freezer; black coated steel exterior

MXM3-72FHC - Reach-in freezer; white coated steel exterior

MXM3-72FBHC - Reach-in freezer; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Triple pane, heated, insulated self-closing glass doors
- Interior LED lighting
- Bottom mounted compressor
- Equipped with eight (8) or twelve (12) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) or six (6) low profile (1.125" x 1.625") rollers (2 or 3 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48FHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	0°F to 10°F (-18°C to -12°C)	6.5A	490 lbs (223 kg)	R-290A 5.29 oz (167 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48FBHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	0°F to 10°F (-18°C to -12°C)	6.5A	490 lbs (223 kg)	R-290A 5.29 oz (167 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM3-72FHC	81" x 32" x 79.5" (2057 x 810 x 2019 mm)	72.25" x 26.5" x 52.25" (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	0°F to 10°F (-18°C to -12°C)	9.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph
MXM3-72FBHC	81" x 32" x 79.5" (2057 x 810 x 2019 mm)	72.25" x 26.5" x 52.25" (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	0°F to 10°F (-18°C to -12°C)	9.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph

COUNTERTOP MERCHANDISER REFRIGERATORS & FREEZERS



MXM1-2RHC
MXM1-2FHC
22.4"W x 22"D x 20.9"H



MXM1-2.5FHC
22.4"W x 22"D x 20.9"H



MXM1-3.5RHC
MXM1-3.5FHC
22.4"W x 22"D x 20.9"H



MXM1-4FHC
22.4"W x 22"D x 20.9"H

Refrigerators:

MXM1-2RHC - Reach-in refrigerator; coated steel exterior

MXM1-3.5RHC - Reach-in refrigerator; coated steel exterior

Freezers:

MXM1-2FHC - Reach-in freezer; coated steel exterior

MXM1-2.5FHC - Reach-in freezer; coated steel exterior

MXM1-3.5FHC - Reach-in freezer; coated steel exterior

MXM1-4FHC - Reach-in freezer; coated steel exterior

All Models Feature:

- Constructed of white painted steel exterior and ABS interior
- Mutli-pane, self-closing glass door with magnetic compression gaskets
- Interior LED lighting
- Bottom mounted compressor
- Equipped with adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) adjustable leveling feet
- Digital controls with LED temperature display
- Automatic defrost cycle
- Provided with lock and key set for security
- Foamed urethane insulation to improve temperature regulation
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-2RHC	22.4" x 22" x 20.9" (569 x 558 x 531 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.1 Cu Ft (59.5 L)	33°F to 41°F (1°C to 5°C)	1.2A	94.8 lbs (43 kg)	R-600A 1.41 oz (40 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-3.5RHC	24.4" x 22" x 27.2" (620 x 558 x 691 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	3.5 Cu Ft (102 L)	33°F to 41°F (1°C to 5°C)	1.2A	117 lbs (53 kg)	R-600A 1.76 oz (50 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-2FHC	22.4" x 22" x 20.9" (569 x 558 x 531 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.1 Cu Ft (59.5 L)	0°F to 10°F (-18°C to -12°C)	1.8A	101.4 lbs (46 kg)	R-600A 1.59 oz (45 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-2.5FHC	22.4" x 22" x 28.7" (569 x 558 x 729 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.6 Cu Ft (73.5 L)	0°F to 10°F (-18°C to -12°C)	1.8A	115 lbs (52 kg)	R-600A 1.59 oz (45 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-3.5FHC	24.4" x 22" x 27.2" (620 x 558 x 691 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	3.5 Cu Ft (102 L)	0°F to 10°F (-18°C to -12°C)	2.5A	123.5 lbs (56 kg)	R-290A 2.29 oz (65 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-4FHC	22.4" x 22" x 35" (569 x 558 x 889 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	4.2 Cu Ft (119 L)	0°F to 10°F (-18°C to -12°C)	2.5A	143 lbs (65 kg)	R-290A 2.29 oz (65 g)	1 / 3	115V / 60Hz / 1Ph



MECR-31D

16.7"W x 15.9"D x 38.6"H



MECR-32D

16.7"W x 15.9"D x 38.6"H

Models:

MECR-31D - Reach-in refrigerator; white coated steel exterior

MECR-32D - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Durable, corrosion resistant black painted steel and stainless steel exterior with black plastic trim
- Easy to clean, low maintenance ABS interior
- Dual pane tempered glass doors and sides prevent heat loss and minimize condensation
- Interior LED lighting
- Digital controls deliver precise temperature regulation
- Internal bottom mounted compressor with flow through ventilation to cool the utility compartment
- Manual defrost cycle maintains ideal storage conditions
- Internal condensate evaporator pan included, so no drain connection is needed
- Flat top accommodates POP or other marketing displays
- Three (3) heavy-duty, adjustable chrome-plated wire shelves
- 2" legs (two front adjustable leveling legs)



MODEL	EXTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MECR-31D	16.7" x 15.9" x 38.6" (425 x 404 x 980 mm)	3 Cu Ft (85 L)	33°F to 54°F (1°C to 12°C)	2.0A	84.9 lbs (38.5 kg)	R-290A 1.41 oz (40 g)	1 / 3	115V / 60Hz / 1Ph
MECR-32D	16.7" x 15.9" x 38.6" (425 x 404 x 980 mm)	3 Cu Ft (85 L)	33°F to 54°F (1°C to 12°C)	2.0A	86 lbs (39 kg)	R-290A 1.41 oz (40 g)	2 / 3	115V / 60Hz / 1Ph



 **MAXX COLD**
X-series

 **MAXX COLD**
SELECT SERIES

UNDERCOUNTER REFRIGERATORS AND FREEZERS

Our undercounter refrigeration options pair reliable cold storage and sturdy construction with valuable countertop space. A variety of sizes are available in both refrigerators and freezers to meet your needs.



MXCR27U-FBHC
27.5"W x 30"D x 31.5"H

MXCR27UHC
MXCF27UHC
27.5"W x 30"D x 35.5"H

MXCR48UHC
MXCF48UHC
48.3125"W x 30"D x 35.5"H

MXCR60UHC
MXCF60UHC
60.375"W x 30"D x 35.5"H

MXCR72UHC
72.375"W x 30"D x 35.5"H

Refrigerators:

- MXCR27UHC** - Undercounter refrigerator; stainless steel exterior
- MXCR27U-FBHC** - Undercounter refrigerator; stainless steel exterior
- MXCR48UHC** - Undercounter refrigerator; stainless steel exterior
- MXCR60UHC** - Undercounter refrigerator; stainless steel exterior
- MXCR72UHC** - Undercounter refrigerator; stainless steel exterior

Freezers:

- MXCF27UHC** - Undercounter freezer; stainless steel exterior
- MXCF48UHC** - Undercounter freezer; stainless steel exterior
- MXCF60UHC** - Undercounter freezer; stainless steel exterior

All Models Feature:

- Durable, easy to clean stainless steel exterior
- Painted aluminum interior
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Equipped with four (4) 3" swivel casters (2 with brakes)
- Solid state digital control system
- LED temperature display
- Accommodates full-size sheet pans
- Automatic defrost system
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane insulated walls and doors
- MXCR27U-FBHC: Compact front-breathing design accommodates tight spaces



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXCR27UHC	27.5" x 30" x 35.5" (699 x 762 x 911 mm)	22.9" x 18.8" x 24.5" (602 x 478 x 622 mm)	6.5 Cu Ft (184 L)	33°F to 41°F (1°C to 5°C)	1.5A	220 lbs (100 kg)	R-600a 2.47 oz (68 g)	1 / 1	115V / 60Hz / 1Ph
MXCR27U-FBHC	27.5" x 30" x 31.5" (700 x 760 x 800 mm)	23.4" x 16.6" x 20.7" (594 x 423 x 525 mm)	6.5 Cu Ft (184 L)	33°F to 41°F (1°C to 5°C)	1.5A	243 lbs (110 kg)	R-600a 2.47 oz (68 g)	1 / 1	115V / 60Hz / 1Ph
MXCR48UHC	48.3125" x 30" x 35.5" (1227 x 762 x 911 mm)	43.5" x 18.8" x 24.5" (1104 x 478 x 622 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	304 lbs (140 kg)	R-600a 2.65 oz (75 g)	2 / 2	115V / 60Hz / 1Ph
MXCR60UHC	60.375" x 30" x 35.5" (1533 x 762 x 911 mm)	56.2" x 18.8" x 24.5" (1428 x 478 x 622 mm)	15.5 Cu Ft (439 L)	33°F to 41°F (1°C to 5°C)	3.0A	352 lbs (160 kg)	R-600a 2.82 oz (80 g)	2 / 2	115V / 60Hz / 1Ph
MXCR72UHC	72.375" x 30" x 35.5" (1839 x 762 x 911 mm)	66.9" x 18.8" x 24.5" (1700 x 478 x 622 mm)	18 Cu Ft (510 L)	33°F to 41°F (1°C to 5°C)	3.5A	430 lbs (195 kg)	R-290a 4.59 oz (130 g)	3 / 3	115V / 60Hz / 1Ph
MXCF27UHC	27.5" x 30" x 35.5" (699 x 762 x 911 mm)	22.9" x 18.8" x 24.5" (602 x 478 x 622 mm)	6.5 Cu Ft (184 L)	-4°F to 10°F (-20°C to -12°C)	1.9A	224 lbs (102 kg)	R-290a 3.35 oz (95 g)	1 / 1	115V / 60Hz / 1Ph
MXCF48UHC	48.3125" x 30" x 35.5" (1227 x 762 x 911 mm)	43.5" x 18.8" x 24.5" (1104 x 478 x 622 mm)	12 Cu Ft (340 L)	-4°F to 10°F (-20°C to -12°C)	4.0A	310 lbs (141 kg)	R-290a 3.53 oz (100 g)	2 / 2	115V / 60Hz / 1Ph
MXCF60UHC	60.375" x 30" x 35.5" (1533 x 762 x 911 mm)	56.2" x 18.8" x 24.5" (1428 x 478 x 622 mm)	15.5 Cu Ft (439 L)	-4°F to 10°F (-20°C to -12°C)	5.0A	362 lbs (166 kg)	R-290a 3.53 oz (100 g)	2 / 2	115V / 60Hz / 1Ph

UNDERCOUNTER REFRIGERATORS & FREEZERS



MXSR29UHC
MXSF29UHC
29"W x 30.3"D x 38.3"H



MXSR48UHC
MXSF48UHC
48"W x 30.3"D x 38.3"H



MXSR60UHC
MXSF60UHC
60"W x 30.3"D x 38.3"H

Refrigerators:

MXSR29UHC - Undercounter refrigerator; stainless steel exterior

MXSR48UHC - Undercounter refrigerator; stainless steel exterior

MXSR60UHC - Undercounter refrigerator; stainless steel exterior

Freezers:

MXSF27UHC - Undercounter freezer; stainless steel exterior

MXSF48UHC - Undercounter freezer; stainless steel exterior

MXSF60UHC - Undercounter freezer; stainless steel exterior

All Models Feature:

- Exterior Material: Durable, easy to clean stainless steel
- Interior Material: Easy to clean painted aluminum
- Environmentally friendly, CFC-free urethane foam insulated walls and doors
- Heavy-duty epoxy coated shelves for easy access and minimal maintenance without disrupting air flow
- Rear-accessed utility compartment provides space efficiency as well as easier servicing while conserving energy consumption
- Easy to grip, stainless steel, self-closing doors with integrated door handles
- Equipped with four (4) Casters (2 with brakes)
- Adjustable shelves (one per section/door)



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT	DOORS / SHELVES	ELECTRICAL
MXSR29UHC	29" x 30.3" x 38.3" (735 x 770 x 976 mm)	24" x 23.4" x 26.6" (610 x 636 x 676 mm)	6.7 Cu Ft (184 L)	33°F to 41°F (1°C to 5°C)	3.6A	143 lbs (65 kg)	R-290a	1 / 1	115V / 60Hz / 1Ph
MXSR48UHC	48" x 30.3" x 38.3" (1230 x 770 x 976 mm)	43" x 23.4" x 26.6" (1105 x 636 x 676 mm)	11.1 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	4.3A	242 lbs (110 kg)	R-290a	2 / 2	115V / 60Hz / 1Ph
MXSR60UHC	61" x 30.3" x 38.3" (1555 x 770 x 976 mm)	56" x 23.4" x 26.6" (1430 x 636 x 676 mm)	14.1 Cu Ft (439 L)	33°F to 41°F (1°C to 5°C)	5.6A	265 lbs (120 kg)	R-290a	2 / 2	115V / 60Hz / 1Ph
MXSF29UHC	29" x 30.3" x 38.3" (735 x 770 x 976 mm)	24" x 23.4" x 26.6" (610 x 636 x 676 mm)	6.7 Cu Ft (184 L)	0°F to 10°F (-18°C to -23°C)	3.6A	143 lbs (65 kg)	R-290a	1 / 1	115V / 60Hz / 1Ph
MXSF48UHC	48" x 30.3" x 38.3" (1230 x 770 x 976 mm)	43" x 23.4" x 26.6" (1105 x 636 x 676 mm)	11.1 Cu Ft (340 L)	0°F to 10°F (-18°C to -23°C)	4.3A	242 lbs (110 kg)	R-290a	2 / 2	115V / 60Hz / 1Ph
MXSF60UHC	61" x 30.3" x 38.3" (1555 x 770 x 976 mm)	56" x 23.4" x 26.6" (1430 x 636 x 676 mm)	14.1 Cu Ft (439 L)	0°F to 10°F (-18°C to -23°C)	5.6A	265 lbs (120 kg)	R-290a	2 / 2	115V / 60Hz / 1Ph



 **MAXX COLD**
SELECT SERIES

CHEST FREEZERS

Store meats and frozen products conveniently with the full line of Select Series Chest Freezers. Featuring easy-to-use controls, our chest freezers are a terrific solution to keep ingredients fresh and accessible.

SOLID-TOP CHEST FREEZERS



MXSH3.4SHC
22.8"W x 22"D x 33.625"H



MXSH5.2SHC
30.4"W x 22"D x 33.625"H



MXSH7.0SHC
37.8"W x 22"D x 33.625"H

Models:

MXSH3.4SHC - Solid-top chest freezer; coated steel exterior

MXSH5.2SHC - Solid-top chest freezer; coated steel exterior

MXSH7.0SHC - Solid-top chest freezer; coated steel exterior

All Models Feature:

- Sturdy hinged top opening lid that opens up to 90°
- Includes lock to provide security even if unattended
- Utilizes R-600A refrigerant
- Equipped with one (1) white wire storage basket
- Supplied with low profile roller wheels
- Can hold the contents safely for 2 days in case of a power outage



MODEL	EXTERNAL DIMENSIONS	CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	LIDS/ BASKETS	ELECTRICAL
MXSH3.4SHC	22.8 x 22 x 33.625 579 x 559 x 854 mm	3.4 Cu Ft (96 L)	-11.2°F to -1°F (-24°C to -18°C)	1.0A	75 lbs (34 kg)	R-600a 1.76 oz (50 g)	1 / 1	115V / 60Hz / 1Ph
MXSH5.2SHC	30.4 x 22 x 33.625 772 x 559 x 854 mm	5.2 Cu Ft (147 L)	-11.2°F to -1°F (-24°C to -18°C)	1.0A	92.6 lbs (42 kg)	R-600a 1.98 oz (56 g)	1 / 1	115V / 60Hz / 1Ph
MXSH7.0SHC	37.8 x 22 x 33.625 960 x 559 x 854 mm	7.0 Cu Ft (198 L)	-11.2°F to -1°F (-24°C to -18°C)	5.6A	99.2 lbs (45 kg)	R-600a 1.90 oz (54 g)	1 / 1	115V / 60Hz / 1Ph



MXSH9.6SHC

40.6"W x 29.7"D x 33.625"H



MXSH12.7SHC

50"W x 29.7"D x 33.625"H



MXSH15.9SHC

60.2"W x 29.7"D x 33.625"H

Models:

MXSH9.6SHC - Solid-top chest freezer; coated steel exterior

MXSH12.7SHC - Solid-top chest freezer; coated steel exterior

MXSH15.9SHC - Solid-top chest freezer; coated steel exterior

All Models Feature:

- Sturdy hinged top opening lid that opens up to 90°
- Includes lock to provide security even if unattended
- Utilizes R-134A refrigerant
- MXSH9.6S, MXSH12.7S: Supplied with one (1) white wire storage basket
- MXSH15.9S: Equipped with two (2) white wire storage baskets
- Supplied with low profile roller wheels
- Can hold the contents safely for 2 days in case of a power outage



MODEL	EXTERNAL DIMENSIONS	CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	LIDS/ BASKETS	ELECTRICAL
MXSH9.6SHC	40.6" x 29.7" x 33.625" 1030 x 755 x 854 mm	9.6 Cu Ft (272 L)	-11.2°F to -1°F (-24°C to -18°C)	1.5A	136.7 lbs (62 kg)	R-600a 2.65 oz (75 g)	1 / 1	115V / 60Hz / 1Ph
MXSH12.7SHC	50" x 29.7" x 33.625" 1270 x 755 x 854 mm	12.7 Cu Ft (360 L)	-11.2°F to -1°F (-24°C to -18°C)	1.5A	152.1 lbs (69 kg)	R-600a 3.0 oz (85 g)	1 / 1	115V / 60Hz / 1Ph
MXSH15.9SHC	60.2" x 29.7" x 33.625" 1530 x 755 x 854 mm	15.9 Cu Ft (450 L)	-11.2°F to -1°F (-24°C to -18°C)	2.6A	185.2 lbs (84 kg)	R-290a 3.2 oz (91 g)	1 / 2	115V / 60Hz / 1Ph

SOLID-TOP CHEST FREEZERS



MXSH19.4SHC
71.3"W x 29.7"D x 33.625"H



MXSH23.6SHC
78.75"W x 29.7"D x 33.625"H



MXSH30.0SHC
76"W x 35.25"D x 35.83"H

Models:

MXSH19.4SHC - Solid-top chest freezer; coated steel exterior

MXSH23.6SHC - Solid-top chest freezer; coated steel exterior

MXSH30.0SHC - Solid-top chest freezer; coated steel exterior

All Models Feature:

- Sturdy hinged top opening lid(s) that opens up to 90°
- Includes lock to provide security even if unattended
- Supplied with two (2) white wire storage baskets
- Equipped with low profile roller wheels
- Can hold the contents safely for 2 days in case of a power outage



MODEL	EXTERNAL DIMENSIONS	CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	LIDS/ BASKETS	ELECTRICAL
MXSH19.4SHC	71.3 x 29.7 x 33.625 1810 x 755 x 854 mm	19.4 Cu Ft (549 L)	-11.2°F to -1°F (-24°C to -18°C)	2.6A	205 lbs (93 kg)	R-290a 3.53 oz (100 g)	1 / 2	115V / 60Hz / 1Ph
MXSH23.6SHC	78.75 x 29.7 x 33.625 2000 x 755 x 854 mm	23.6 Cu Ft (669 L)	-11.2°F to -1°F (-24°C to -18°C)	2.1A	198.4 lbs (90 kg)	R-290a 4.94 oz (140 g)	2 / 2	115V / 60Hz / 1Ph
MXSH30.0SHC	76 x 35.25 x 35.83 1930 x 895 x 910 mm	30.0 Cu Ft (850 L)	-11.2°F to -1°F (-24°C to -18°C)	2.1A	242.5 lbs (110 kg)	R-290a 5.29 oz (150 g)	2 / 2	115V / 60Hz / 1Ph



 **MAXX COLD**
X-series

DIPPING CABINETS & ICE CREAM DISPLAY FREEZERS

Display and store ice cream, gelato, sorbet and frozen treats with Maxx Cold Dipping Cabinets and Mobile Ice Cream Freezers. The glass top design and LED lights illuminate and enhance your products, while the heat reflective glass ensures consistent temperature.

ICE CREAM DIPPING CABINETS



MXDC-4
31.5"W x 27.2"D x 50.4"H



MXDC-8
51.7"W x 27.2"D x 50.4"H



MXDC-12
70"W x 27.2"D x 50.4"H

Models:

MXDC-4 - Dipping cabinet; coated steel exterior

MXDC-8 - Dipping cabinet coated steel exterior

MXDC-12 - Dipping cabinet; coated steel exterior

All Models Feature:

- Flat, tempered clear glass sliding lids
- Lid lock and keys with removable pin to keep lid unlocked
- Interior LED lights makes it easier to see selection and enhance product's appearance
- Curved tempered glass sneeze guard (assembly required)
- Molded plastic lid frame heated to prevent frost or ice build-up
- Supplied with internal condensate evaporator pan, there is no need for a floor drain
- Bottom defrost drain with plug
- Heavy-duty casters, two locking
- Removable rubber bumper guards and side grill
- Adjustable temperature range -18°F to +10°F (-28°C to -12°C)
- Thermometer display: external, digital, easily read
- Exterior Material: durable, white powder coated steel
- Interior Material: pre-coated white steel
- Tub Holders: Powder coated, wire
- Includes: Hanging tub holders and spill skirts
- Insulation: Thick, 2.5" foamed in-place, environmentally friendly polyurethane

Available Accessories:

- Dipper well with faucet #XDCWELL



- Zeroll® scoops and spades (Various models available - inquire for info)



- Gelato pans #XDPCAN-5



- Gelato pan holders & Novelty baskets #XDCBASKET3 / #XDCBASKETN3



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	TOTAL TUB STORAGE	TUBS EXPOSED FOR SCOOPING	ELECTRICAL
MXDC-4	31.5" x 27.2" x 50.4" (800 x 691 x 1280 mm)	25.5" x 21.5" x 26.5" (648 x 546 x 673 mm)	6.5 Cu Ft (184 L)	-18°F to 10°F (-28°C to -12°C)	1.3A	184 lbs (83 kg)	R290 2.65 oz (75 g)	6	4	115V / 60Hz / 1Ph
MXDC-8	51.7" x 27.2" x 50.4" (1313 x 691 x 1280 mm)	46.5" x 21.5" x 26.5" (1181 x 546 x 673 mm)	8.8 Cu Ft (249 L)	-18°F to 10°F (-28°C to -12°C)	2.0A	262 lbs (119 kg)	R290 3.6 oz (102 g)	14	8	115V / 60Hz / 1Ph
MXDC-12	70" x 27.2" x 50.4" (1778 x 691 x 1280 mm)	65.5" x 21.5" x 26.5" (1664 x 546 x 673 mm)	11.1 Cu Ft (314 L)	-18°F to 10°F (-28°C to -12°C)	4.1A	320 lbs (145 kg)	R290 4.76 oz (135 g)	22	12	115V / 60Hz / 1Ph



MXF31F

31.5"W x 27.2"D x 50.4"H



MXF52F

51.7"W x 27.2"D x 50.4"H



MXF71F

70"W x 27.2"D x 50.4"H

Models:

MXF31F - Mobile ice cream freezer; coated steel exterior

MXF52F - Mobile ice cream freezer; coated steel exterior

MXF71F - Mobile ice cream freezer; coated steel exterior

All Models Feature:

- Flat, tempered clear glass sliding lids
- Lid lock and keys
- Interior LED lights makes it easier to see selection and enhance product's appearance
- Molded plastic lid frame heated to prevent frost or ice build-up
- Equipped with internal condensate evaporator pan, there is no need for a floor drain
- Bottom defrost drain with plug
- Dual heavy-duty casters, two locking
- Removable rubber bumper guards, side grill
- Adjustable temperature range -18°F to +10°F (-28°C to -12°C)
- Thermometer display: external, analog, easily read
- Exterior Material: durable, white zinc coated, baked on enamel steel
- Interior Material: painted white power coated steel
- Flat wire baskets with 3 compartments
- Insulation: Thick, 2.5" foamed in-place, environmentally friendly, polyurethane
- Includes: Novelty baskets



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	BASKETS	ELECTRICAL
MXF31F	31.5" x 27.2" x 50.4" (800 x 690 x 1280 mm)	25.5" x 21.5" x 26.5" (648 x 546 x 673 mm)	5.8 Cu Ft (164 L)	-18°F to 10°F (-28°C to -12°C)	1.3A	130 lbs (59 kg)	R290 2.65 oz (75 g)	2	115V / 60Hz / 1Ph
MXF52F	51.7" x 27.2" x 50.4" (1313 x 690 x 1280 mm)	40" x 25.2" x 13.9" (1017 x 639 x 353 mm)	11 Cu Ft (312 L)	-18°F to 10°F (-28°C to -12°C)	2.0A	179 lbs (81 kg)	R290 3.6 oz (102 g)	4	115V / 60Hz / 1Ph
MXF71F	70" x 27.2" x 50.4" (1778 x 690 x 1280 mm)	52" x 25.2" x 13.9" (1320 x 639 x 353 mm)	16 Cu Ft (453 L)	-18°F to 10°F (-28°C to -12°C)	4.1A	219 lbs (99 kg)	R290 4.76 oz (135 g)	5	115V / 60Hz / 1Ph

MOBILE ICE CREAM FREEZERS



MXF25CHC-2
24.6"W x 27.6"D x 32.6"H



MXF32CHC-3
31.5"W x 27.5"D x 33.5"H



MXF40CHC-4
39.4"W x 27.5"D x 33.5"H



MXF48CHC-5
47.4"W x 27.5"D x 33.5"H



MXF54CHC-6
53.2"W x 27.5"D x 33.5"H



MXF64CHC-7
63.4"W x 27.5"D x 33.5"H



MXF72CHC-8
71.7"W x 27.5"D x 33.5"H

Models:

MXF25CHC-2 - Mobile ice cream freezer; coated steel exterior

MXF32CHC-3 - Mobile ice cream freezer; coated steel exterior

MXF40CHC-4 - Mobile ice cream freezer; coated steel exterior

MXF48CHC-5 - Mobile ice cream freezer; coated steel exterior

MXF54CHC-6 - Mobile ice cream freezer; coated steel exterior

MXF64CHC-7 - Mobile ice cream freezer; coated steel exterior

MXF72CHC-8 - Mobile ice cream freezer; coated steel exterior

All Models Feature:

- Clear, curved glass sliding lids
- Easy grip sliding lid handle
- Lid lock and keys
- Interior LED lights makes it easier to see selection and enhance product's appearance
- Molded plastic lid frame heated to prevent frost or ice build-up
- Internal condensate evaporator pan. No need for a floor drain.
- Equipped with four (4) or six (6) heavy-duty casters
- Removable rubber bumper guards, side grill



MODEL	EXTERIOR DIMENSIONS	CAPACITY	HOLDING TEMPERATURE RANGE	REFRIGERANT AND CHARGE SIZE	UNIT WEIGHT	AMP DRAW	HP	INCLUDED BASKETS
MXF25CHC-2	24.6 x 27.6 x 32.6 625 x 700 x 828 mm	3.81 Cu Ft 108 L	-18°F to 10°F (-28°C to -12°C)	R290a 2.43 oz / 69 g	103.6 lb 47 kg	1.0A	1/9	2
MXF32CHC-3	31.5 x 27.5 x 33.5 800 x 697 x 850 mm	4.87 Cu Ft 138 L	-18°F to 10°F (-28°C to -12°C)	R290a 2.65 oz / 75 g	114.6 lb 52 kg	1.3A	1/7	3
MXF40CHC-4	39.4 x 27.5 x 33.5 1000 x 697 x 850 mm	6.71 Cu Ft 190 L	-18°F to 10°F (-28°C to -12°C)	R290a 3 oz / 85 g	130.1 lb 59 kg	1.4A	1/5	4
MXF48CHC-5	47.4 x 27.5 x 33.5 1204 x 697 x 850 mm	8.62 Cu Ft 244 L	-18°F to 10°F (-28°C to -12°C)	R290a 3.53 oz / 100 g	152.1 lb 69 kg	2.0A	1/4	5
MXF54CHC-6	53.2 x 27.5 x 33.5 1350 x 697 x 850 mm	9.96 Cu Ft 282 L	-18°F to 10°F (-28°C to -12°C)	R290a 4.06 oz / 115 g	165.4 lb 75 kg	2.0A	1/4	6
MXF64CHC-7	63.4 x 27.5 x 33.5 1610 x 697 x 850 mm	12.36 Cu Ft 350 L	-18°F to 10°F (-28°C to -12°C)	R290a 4.23 oz / 120 g	187.4 lb 85 kg	2.0A	1/4+	7
MXF72CHC-8	71.7 x 27.5 x 33.5 1820 x 697 x 850 mm	14.30 Cu Ft 405 L	-18°F to 10°F (-28°C to -12°C)	R290a 4.76 oz / 135 g	231.5 lb 105 kg	2.8A	1/2	8



 **MAXX COLD**
X-series

 **MAXX COLD**
SELECT SERIES

PREP TABLES

Maxx Cold Food Preparation Tables are available in a variety of capacities and styles, designed to meet the needs of any commercial kitchen. Choose from Sandwich/Salad Stations, expanded capacity Megatop units, or Pizza Prep tables.

SANDWICH / SALAD STATIONS



MXCR29SHC
28.9"W x 29.9"D x 43.2"H



MXCR48SHC
48.2"W x 29.9"D x 43.2"H



MXCR60SHC
61.2"W x 29.9"D x 43.2"H



MXCR72SHC
71.7"W x 29.9"D x 43.2"H

Models:

MXCR29SHC - Sandwich station; stainless steel exterior

MXCR48SHC - Sandwich station; stainless steel exterior

MXCR60SHC - Sandwich station; stainless steel exterior

MXCR72SHC - Sandwich station; stainless steel exterior

All Models Feature:

- Stainless steel exterior and powder coated aluminum interior construction
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Supplied with four (4) 3" swivel casters (2 with brakes)
- Equipped with full set of clip-on divider bars and 4" deep plastic pans (not compatible with pans deeper than 4")
- Supplied with 11.42" deep polyethylene cutting board
- Solid state digital control system
- LED temperature display
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	PANS (1/6)	ELECTRICAL
MXCR29SHC	28.9" x 29.9 x 43.2" (699 x 760 x 1098 mm)	22.9" x 18.8" x 24.5" (602 x 478 x 622 mm)	7 Cu Ft (198 L)	33°F to 41°F (1°C to 5°C)	3.0A	218 lbs (99 kg)	R290a 3.0 oz (85 g)	1 / 1	8	115V / 60Hz / 1Ph
MXCR48SHC	48.2" x 29.9 x 43.2" (1225 x 760 x 1098 mm)	43.5" x 18.8" x 24.5" (1104 x 478 x 622 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	4.3A	304 lbs (140 kg)	R-290a 3.17 oz (90 g)	2 / 2	12	115V / 60Hz / 1Ph
MXCR60SHC	61.2" x 29.9 x 43.2" (1555 x 760 x 1098 mm)	56.2" x 18.8" x 24.5" (1428 x 478 x 622 mm)	15.5 Cu Ft (439 L)	33°F to 41°F (1°C to 5°C)	4.3A	352 lbs (160 kg)	R-290a 3.17 oz (90 g)	2 / 2	16	115V / 60Hz / 1Ph
MXCR72SHC	71.7" x 29.9 x 43.2" (1822 x 760 x 1098 mm)	66.9" x 18.8" x 24.5" (1700 x 478 x 622 mm)	18 Cu Ft (510 L)	33°F to 41°F (1°C to 5°C)	4.3A	430 lbs (195 kg)	R-290a 3.35 oz (95 g)	3 / 3	18	115V / 60Hz / 1Ph



MXSR29SHC
29"W x 30.3"D x 45.4"H



MXSR48SHC
48.4"W x 30.3"D x 45.4"H



MXSR60SHC
61.2"W x 30.3"D x 45.4"H

Models:

MXSR29SHC - Sandwich station; stainless steel exterior

MXSR48SHC - Sandwich station; stainless steel exterior

MXSR60SHC - Sandwich station; stainless steel exterior

All Models Feature:

- Durable, easy to clean stainless steel exterior and interior
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Supplied with four (4) 6" swivel casters (2 with brakes)
- Equipped with full set of pans
- Automatic defrost system
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Equipped with a food grade plastic cutting board and full set of clip-on divider bars and plastic pans
- Self-closing doors
- Polyurethane insulated doors and walls
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT	PAN CAPACITY 1/3 (1/6)	DOORS / SHELVES	ELECTRICAL
MXSR29SHC	29" x 30.3" x 45.4" (735 x 770 x 1152 mm)	24" x 23.4" x 26.6" (610 x 636 x 676 mm)	7.59 Cu Ft (215 L)	33°F to 41°F (1°C to 5°C)	3.6A	150 lbs (68 kg)	R-290a	4 (8)	1 / 1	115V / 60Hz / 1Ph
MXSR48SHC	48" x 30.3" x 45.4" (1230 x 770 x 1152 mm)	43" x 23.4" x 26.6" (1105 x 636 x 676 mm)	13.8 Cu Ft (390 L)	33°F to 41°F (1°C to 5°C)	4.3A	256 lbs (116 kg)	R-290a	6 (12)	2 / 2	115V / 60Hz / 1Ph
MXSR60SHC	61" x 30.3" x 45.4" (1555 x 770 x 1152 mm)	56" x 23.4" x 26.6" (1430 x 636 x 676 mm)	17.8 Cu Ft (505 L)	33°F to 41°F (1°C to 5°C)	5.6A	298 lbs (135 kg)	R-290a	8 (16)	2 / 2	115V / 60Hz / 1Ph

MEGATOP PREP TABLES



MXCR29MHC
28.9"W x 34.5"D x 43.2"H



MXCR48MHC
28.9"W x 34.5"D x 43.2"H



MXCR60MHC
61.2"W x 34.5"D x 43.2"H



MXCR72MHC
71.7"W x 34.5"D x 43.2"H

Models:

MXCR29MHC - Megatop prep table; stainless steel exterior

MXCR48MHC - Megatop prep table; stainless steel exterior

MXCR60MHC - Megatop prep table; stainless steel exterior

MXCR72MHC - Megatop prep table; stainless steel exterior

All Models Feature:

- Stainless steel exterior and powder coated aluminum interior construction
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Equipped with four (4) 3" swivel casters (2 with brakes)
- Supplied with full set of clip-on divider bars and 4" deep plastic pans
- Expanded pan capacity compared to standard sandwich prep tables
- Supplied with 9" deep polyethylene cutting board
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	PANS (1/6)	ELECTRICAL
MXCR29MHC	28.9" x 34.5 x 43.2" (699 x 877 x 1098 mm)	22.9" x 18.8" x 24.5" (602 x 478 x 622 mm)	7 Cu Ft (198 L)	33°F to 41°F (1°C to 5°C)	3.0A	220 lbs (100 kg)	R290a 3.0 oz (85 g)	1 / 1	12	115V / 60Hz / 1Ph
MXCR48MHC	48.2" x 34.5 x 43.2" (1225 x 877 x 1098 mm)	43.5" x 18.8" x 24.5" (1104 x 478 x 622 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	4.3A	304 lbs (140 kg)	R-290a 3.17 oz (90 g)	2 / 2	18	115V / 60Hz / 1Ph
MXCR60MHC	61.2" x 34.5 x 43.2" (1555 x 877 x 1098 mm)	56.2" x 18.8" x 24.5" (1428 x 478 x 622 mm)	15.5 Cu Ft (439 L)	33°F to 41°F (1°C to 5°C)	4.3A	352 lbs (160 kg)	R-290a 3.17 oz (90 g)	2 / 2	24	115V / 60Hz / 1Ph
MXCR72MHC	71.7" x 34.5 x 43.2" (1822 x 877 x 1098 mm)	66.9" x 18.8" x 24.5" (1700 x 478 x 622 mm)	18 Cu Ft (510 L)	33°F to 41°F (1°C to 5°C)	4.3A	430 lbs (195 kg)	R-290a 3.35 oz (95 g)	3 / 3	27	115V / 60Hz / 1Ph



MXCPP50HC
47.4"W x 33"D x 41.7"H



MXCPP70HC
70.8"W x 33"D x 41.7"H



MXCPP92HC
94.2"W x 33"D x 41.7"H

Models:

MXCPP50HC - Pizza prep table; stainless steel exterior

MXCPP70HC - Pizza prep table; stainless steel exterior

MXCPP92HC - Pizza prep table; stainless steel exterior

All Models Feature:

- Stainless steel exterior and powder coated aluminum interior construction
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Supplied with four (4) 3" swivel casters (2 with brakes)
- Equipped with full set of clip-on divider bars and 4" deep plastic pans (can accommodate up to 6" deep pans)
- Supplied with 17.75" deep polyethylene cutting board
- Solid state digital control system
- LED temperature display
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL CABINET DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	PANS (1/3)	ELECTRICAL
MXCPP50HC	47.4" x 33 x 41.7" (1212 x 838 x 1059 mm)	26" x 27.75" x 24" (660 x 705 x 610 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	5.0A	348 lbs (158 kg)	R-290a 3.7 oz (105 g)	1 / 1	6	115V / 60Hz / 1Ph
MXCPP70HC	70.8" x 33 x 41.7" (1798 x 838 x 1059 mm)	49.5" x 27.75" x 24" (1257 x 705 x 610 mm)	22 Cu Ft (623 L)	33°F to 41°F (1°C to 5°C)	5.0A	432 lbs (196 kg)	R-290a 3.7 oz (105 g)	2 / 2	9	115V / 60Hz / 1Ph
MXCPP92HC	94.2" x 33 x 41.7" (2393 x 838 x 1059 mm)	73" x 27.75" x 24" (1854 x 705 x 610 mm)	32 Cu Ft (906 L)	33°F to 41°F (1°C to 5°C)	5.5A	582 lbs (264 kg)	R-290a 3.7 oz (105 g)	3 / 3	12	115V / 60Hz / 1Ph

PIZZA PREP TABLES



MXSPP50HC
47"W x 34.6"D x 42"H



MXSPP70HC
71"W x 34.6"D x 42"H



MXSPP92HC
94"W x 34.6"D x 42"H

Models:

MXSPP50HC - Pizza prep table; stainless steel exterior

MXSPP70HC - Pizza prep table; stainless steel exterior

MXSPP92HC - Pizza prep table; stainless steel exterior

All Models Feature:

- Exterior Material: Durable, easy to clean stainless steel
- Interior Material: Coated aluminum
- Environmentally friendly, CFC-free urethane foam insulated walls and doors
- Supplied with four (4) 6" swivel casters (2 with brakes)
- Equipped with full set of plastic pans
- Standard recessed door handles
- Heavy duty epoxy coated shelves for easy access and minimal maintenance without disrupting air flow
- Front-accessed utility compartment for easy maintenance & effective air movement to properly cool the condensing unit
- Easily replaceable dart-style magnetic compression gaskets



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT	PAN CAPACITY 1/3 (1/6)	DOORS / SHELVES	ELECTRICAL
MXSPP50HC	47" x 34.6" x 42" (1200 x 880 x 1068 mm)	25.6" x 27.8" x 26.5" (650 x 707 x 672 mm)	10.9 Cu Ft (310 L)	33°F to 41°F (1°C to 5°C)	4A	201 lbs (91 kg)	R-290a	6 (12)	1 / 1	115V / 60Hz / 1Ph
MXSPP70HC	71" x 34.6" x 42" (1795 x 880 x 1068 mm)	49" x 27.8" x 26.5" (1245 x 707 x 672 mm)	20.9 Cu Ft (592 L)	33°F to 41°F (1°C to 5°C)	5.8A	342 lbs (155 kg)	R-290a	9 (18)	2 / 2	115V / 60Hz / 1Ph
MXSPP92HC	94" x 34.6" x 42" (2390 x 880 x 1068 mm)	72.4" x 27.8" x 26.5" (1840 x 707 x 672 mm)	30.9 Cu Ft (874 L)	33°F to 41°F (1°C to 5°C)	5.8A	485 lbs (220 kg)	R-290a	12 (24)	3 / 3	115V / 60Hz / 1Ph



 **MAXX COLD**
X-series

CHEF BASES

Maxx Cold Chef Bases help to optimize your space and keep key ingredients close at hand. Our chef bases offer plenty of storage and when paired with a countertop grill or work surface are part of an efficient kitchen work station

CHEF BASES



MXCB48HC
50"W x 31.9"D x 26"H



MXCB60HC
62"W x 31.9"D x 26"H



MXCB72HC
74"W x 31.9"D x 26"H

Models:

MXCB48HC - Chef base; stainless steel exterior

MXCB60HC - Chef base; stainless steel exterior

MXCB72HC - Chef base; stainless steel exterior

All Models Feature:

- Constructed of stainless steel
- Easy to grip recessed door handles
- Full extension, heavy-duty drawer slides
- Supplied with four (4) 5" swivel casters (two with brakes)
- Drawer depth 7.9" (200 mm), can accommodate 4" deep pans
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DRAWERS	ELECTRICAL
MXCB48HC	50" x 31.9" x 26" (1270 x 810 x 660 mm)	27.8" x 25.2" x 13.9" (707 x 639 x 353 mm)	6.5 Cu Ft (184 L)	33°F to 41°F (1°C to 5°C)	2.1A	260 lbs (118 kg)	R290a 2.82 oz (80 g)	2	115V / 60Hz / 1Ph
MXCB60HC	62" x 31.9" x 26" (1576 x 810 x 660 mm)	40" x 25.2" x 13.9" (1017 x 639 x 353 mm)	8.8 Cu Ft (249 L)	33°F to 41°F (1°C to 5°C)	2.1A	302 lbs (137 kg)	R-290a 2.82 oz (80 g)	2	115V / 60Hz / 1Ph
MXCB72HC	74" x 31.9" x 26" (1880 x 810 x 660 mm)	52" x 25.2" x 13.9" (1320 x 639 x 353 mm)	11.1 Cu Ft (314 L)	33°F to 41°F (1°C to 5°C)	2.1A	353 lbs (160 kg)	R-290a 2.82 oz (80 g)	4	115V / 60Hz / 1Ph



 **MAXX COLD**
X-series

MILK COOLERS

Maxx Cold Milk Coolers are perfect for any school lunchroom, university dining hall or cafeteria dinning setting. Our milk coolers are available in three models, holding up to 16 milk crates, providing quick, easy access.

MILK COOLERS



MXMC34HC
34"W x 30.6"D x 42"H



MXMC49HC
49"W x 30.6"D x 42"H



MXMC58HC
58"W x 30.6"D x 42"H

Models:

MXMC34HC - Milk cooler; stainless steel exterior

MXMC49HC - Milk cooler; stainless steel exterior

MXMC58HC - Milk cooler; stainless steel exterior

All Models Feature:

- All stainless steel construction
- Supplied with four 4" swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and door
- Accommodates standard 13" x 13" x 11" or 19" x 13" x 11" crates



MODEL	EXTERNAL DIMENSIONS	CAPACITY (13" X 13" X 11" CRATES)	CAPACITY (19" X 13" X 11" CRATES)	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	ELECTRICAL
MXMC34HC	34" x 30.6" x 42" (865 x 777 x 1067 mm)	8	4	36°F to 38°F (2°C to 3°C)	3.0A	220 lbs (100 kg)	R-290a 3.17 oz (90 g)	115V / 60Hz / 1Ph
MXMC49HC	49" x 30.6" x 42" (1245 x 777 x 1067 mm)	12	8	36°F to 38°F (2°C to 3°C)	3.0A	304 lbs (140 kg)	R-290a 3.17 oz (90 g)	115V / 60Hz / 1Ph
MXMC58HC	58" x 30.6" x 42" (1475 x 777 x 1067 mm)	16	10	36°F to 38°F (2°C to 3°C)	3.0A	430 lbs (195 kg)	R-290a 3.17 oz (90 g)	115V / 60Hz / 1Ph



 **MAXX COLD**
X-series

BOTTLE COOLERS AND BEER TOWER DISPENSERS

A benefit to any entertainment establishment, bar or restaurant, serve your customers cold, refreshing beverages with Maxx Cold Bottle Coolers. Maxx Cold Back Bar Coolers provide plenty storage, accurate temperature control and easy access. Maxx Cold Beer Towers are ideal for cold beer dispensing, and are available in multiple sizes to suit any application.



MXCR50BHC
49.4"W x 27"D x 35"H



MXCR65BHC
64.3"W x 27"D x 35"H

Models:

MXCR50BHC - Bottle cooler; black painted steel and stainless steel exterior

MXCR65BHC - Bottle cooler; black painted steel and stainless steel exterior

All Models Feature:

- Reinforced heavy-duty crossbar can support heavy loads without breaking
- External built-in bottle opener and bottle cap catcher
- Rear stainless steel top with marine edge for storing glasses, garnishes/condiments, etc.
- Supplied with two (2) sliding lids for easy access
- Rounded internal edges for easy cleaning
- LED lighting: Bright, long lasting and energy efficient
- Forced air cooling for high efficiency, rapid product cooling and reliable, consistent temperature control
- Uses an environmentally friendly, high r-value, efficient foam insulation to provide years of reliable, cost effective operation
- Designed with sturdy 1" rollers



MODEL	EXTERIOR DIMENSIONS	NET CAPACITY	CAN / BOTTLE CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	LIDS / DIVIDERS	ELECTRICAL
MXCR50HC	49.4" x 27" x 35" (1255 x 686 x 889 mm)	14 Cu Ft (396 L)	504 Cans 336 Bottles	33°F to 41°F (1°C to 5°C)	3A	205 lb 93 kg	R-600a 2.47 oz (70 g)	2 / 2	115V / 60Hz / 1Ph
MXCR65HC	64.3" x 27" x 35" (1633 x 686 x 889 mm)	17 Cu Ft (481 L)	768 Cans 504 Bottles	33°F to 41°F (1°C to 5°C)	3A	280 lb 128 kg	R-600a 3.17 oz (90 g)	2 / 2	115V / 60Hz / 1Ph



MXBD24-1BHC
23.3"W x 29.9"D x 51.7"H



MXBD48-1BHC
47.5"W x 24.4"D x 56"H



MXBD60-1BHC
61.06"W x 24.4"D x 56"H



MXBD24-1SHC
23.3"W x 29.9"D x 51.7"H



MXBD48-1SHC
47.5"W x 24.4"D x 56"H



MXBD60-1SHC
61.06"W x 24.4"D x 56"H

Models:

MXBD24-1BHC - Beer tower dispenser; black coated steel exterior

MXBD48-1BHC - Beer tower dispenser; black coated steel exterior

MXBD60-1BHC - Beer tower dispenser; black coated steel exterior

Stainless Steel Models:

MXBD24-1SHC - Beer tower dispenser; stainless steel exterior

MXBD48-1SHC - Beer tower dispenser; stainless steel exterior

MXBD60-1SHC - Beer tower dispenser; stainless steel exterior

All Models Feature:

- Constructed of powder-coated steel exterior (black) and interior (white)
- Stainless steel interior floor plate
- 3" (77mm) diameter stainless steel insulated beer towers
- Locking door(s) with easy to grip recessed door handles
- Supplied with four (4) swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system

All Models Feature:

- Constructed of stainless steel exterior and white powder-coated interior
- Stainless steel interior floor plate
- 3" (77mm) diameter stainless steel insulated beer towers
- Locking door(s) with easy to grip recessed door handles
- Supplied with four (4) swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / TOWERS / TAP FAUCETS	ELECTRICAL
MXBD24-1BHC	23.3" x 29.9" x 51.65" (592 x 760 x 1312 mm)	7.2 Cu Ft (204 L)	33°F to 41°F (1°C to 5°C)	2.2A	161 lbs (73 kg)	R-600a 2.82 oz (80 g)	1 / 1 / 1	115V / 60Hz / 1Ph
MXBD48-1BHC	47.5" x 24.4" x 56" (1205 x 620 x 1422 mm)	10.5 Cu Ft (297 L)	33°F to 41°F (1°C to 5°C)	3.0A	264 lbs (120 kg)	R-290a 3.88 oz (110 g)	2 / 1 / 2	115V / 60Hz / 1Ph
MXBD60-1BHC	61.06" x 24.4" x 56" (1247 x 620 x 1422 mm)	14.2 Cu Ft (402 L)	33°F to 41°F (1°C to 5°C)	3.0A	302 lbs (137 kg)	R-290a 3.88 oz (110 g)	2 / 1 / 2	115V / 60Hz / 1Ph
MXBD24-1SHC	23.3" x 29.9" x 51.65" (592 x 760 x 1312 mm)	7.2 Cu Ft (204 L)	33°F to 41°F (1°C to 5°C)	2.2A	161 lbs (73 kg)	R-600a 2.82 oz (80 g)	1 / 1 / 1	115V / 60Hz / 1Ph
MXBD48-1SHC	47.5" x 24.4" x 56" (1205 x 620 x 1422 mm)	10.5 Cu Ft (297 L)	33°F to 41°F (1°C to 5°C)	3.0A	264 lbs (120 kg)	R-290a 3.88 oz (110 g)	2 / 1 / 2	115V / 60Hz / 1Ph
MXBD60-1SHC	61.06" x 24.4" x 56" (1247 x 620 x 1422 mm)	14.2 Cu Ft (402 L)	33°F to 41°F (1°C to 5°C)	3.0A	302 lbs (137 kg)	R-290a 3.88 oz (110 g)	2 / 1 / 2	115V / 60Hz / 1Ph

BEER TOWER DISPENSERS - DUAL TOWER



MXBD48-2BHC
47.5"W x 24.4"D x 56"H

MXBD60-2BHC
61.06"W x 24.4"D x 56"H

MXBD72-2BHC
61.06"W x 24.4"D x 56"H

MXBD48-2SHC
47.5"W x 24.4"D x 56"H

MXBD60-2SHC
61.06"W x 24.4"D x 56"H

MXBD72-2SHC
61.06"W x 24.4"D x 56"H

Models:

MXBD48-2BHC - Beer tower dispenser; black coated steel exterior

MXBD60-2BHC - Beer tower dispenser; black coated steel exterior

MXBD72-2BHC - Beer tower dispenser; black coated steel exterior

Stainless Steel Models:

MXBD48-2SHC - Beer tower dispenser; stainless steel exterior

MXBD60-2SHC - Beer tower dispenser; stainless steel exterior

MXBD72-2SHC - Beer tower dispenser; stainless steel exterior

All Models Feature:

- Constructed of powder-coated steel exterior (black) and interior (white)
- Stainless steel interior floor plate
- 3" (77mm) diameter stainless steel insulated beer towers
- Locking door(s) with easy to grip recessed door handles
- Supplied with four (4) or six (6) swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system

All Models Feature:

- Constructed of stainless steel exterior and white powder-coated interior
- Stainless steel interior floor plate
- 3" (77mm) diameter stainless steel insulated beer towers
- Locking door(s) with easy to grip recessed door handles
- Supplied with four (4) or six (6) swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / TOWERS / TAP FAUCETS	ELECTRICAL
MXBD48-2BHC	47.5" x 24.4" x 56" (1205 x 620 x 1422 mm)	10.5 Cu Ft (297 L)	33°F to 41°F (1°C to 5°C)	3.0A	267 lbs (121 kg)	R-290a 3.88 oz (110 g)	2 / 2 / 2	115V / 60Hz / 1Ph
MXBD60-2BHC	61.06" x 24.4" x 56" (1247 x 620 x 1422 mm)	14.2 Cu Ft (402 L)	33°F to 41°F (1°C to 5°C)	3.0A	304 lbs (138 kg)	R-290a 3.88 oz (110 g)	2 / 2 / 2	115V / 60Hz / 1Ph
MXBD72-2BHC	73.07" x 24.4" x 56" (1856 x 620 x 1422 mm)	17.3 Cu Ft (490 L)	33°F to 41°F (1°C to 5°C)	3.0A	351 lbs (159 kg)	R-290a 4.59 oz (130 g)	3 / 2 / 4	115V / 60Hz / 1Ph
MXBD48-2SHC	47.5" x 24.4" x 56" (1205 x 620 x 1422 mm)	10.5 Cu Ft (297 L)	33°F to 41°F (1°C to 5°C)	3.0A	267 lbs (121 kg)	R-290a 3.88 oz (110 g)	2 / 2 / 2	115V / 60Hz / 1Ph
MXBD60-2SHC	61.06" x 24.4" x 56" (1247 x 620 x 1422 mm)	14.2 Cu Ft (402 L)	33°F to 41°F (1°C to 5°C)	3.0A	304 lbs (138 kg)	R-290a 3.88 oz (110 g)	2 / 2 / 2	115V / 60Hz / 1Ph
MXBD72-2SHC	73.07" x 24.4" x 56" (1856 x 620 x 1422 mm)	17.3 Cu Ft (490 L)	33°F to 41°F (1°C to 5°C)	3.0A	351 lbs (159 kg)	R-290a 4.59 oz (130 g)	3 / 2 / 4	115V / 60Hz / 1Ph



MAXX COLD



A DIVISION OF
THE LEGACY COMPANIES

3355 Enterprise Avenue • Suite 160 | Fort Lauderdale, FL 33331
Tel: 954.202.7419 | Fax: 954.202.7337 | www.maxx-cold.com

